Laundry Care p. 3 – 7

Dish & Glass Care p. 8 – 10

Food & Beverage p. 11 – 13

Cooling p. 14 – 19

Floor Care p. 20 – 23

Technical Information Charts p. 24 – 31

Superior Laundry Care
- *Miele's unique Honeycomb drum with up to 6 kg capacity.*
- *Special Programmes: Handwash and Silks*

Peace of mind:
- *Unsurpassed Miele Quality*
- *Patented automatic programmes for ultimate convenience*

W 1513 Novotronic Washing Machine

DESIGN
Straight fascia
5 kg drum capacity
Extra large door opening
Enamel front with powder coated sides
H x W x D: 85 x 59.5 x 63.4 cm

CONTROLS
Single programme selector dial
programme sequence indicator
time left display
PC update facility

SPECIAL PROGRAMMES
Cottons, Minimum iron, Delicates, Automatic, Separate rinse, Drain/Spin, Starch, Handwashable woollens, Silks

ADDITIONAL FUNCTIONS
Water plus, short, pre-wash

SPIN
400–1300 rpm spin speeds
rinse hold & without spin

SAFETY FEATURES
Child resistant controls
water control system
check water inlet & drain indicators,
detergent overdosing indicator

CONSUMPTION
45 litre water

W 526 Novotronic Washing Machine

DESIGN
Straight fascia
5 kg drum capacity
Extra large door opening
Direct enamel casing
H x W x D: 85 x 59.5 x 58 cm

CONTROLS
Single programme selector dial
programme sequence indicator
time left display
PC update facility

SPECIAL PROGRAMMES
Cottons, Minimum iron, Delicates, Automatic, Separate rinse, Drain/Spin, Starch, Quickwash, Handwashable woollens, Silks

ADDITIONAL FUNCTIONS
Water plus, short, pre-wash, soak

SPIN
400–1400 rpm spin speeds
rinse hold & without spin

SAFETY FEATURES
Child resistant controls
water control system
check water inlet & drain indicators,
detergent overdosing indicator

CONSUMPTION
45 litre water, 0.85 kWh electricity

W 3240 Honeycomb Care Washing Machine

DESIGN
Straight fascia
Unique Miele Honeycomb Drum with
6 kg capacity
Extra large door opening
Direct enamel casing
H x W x D: 85 x 59.5 x 58 cm

CONTROLS
Single programme selector dial
programme sequence indicator
time left display
PC update facility

SPECIAL PROGRAMMES
Cottons, Minimum iron, Dark, Denims, Shirt, Delicates, Automatic, Separate rinse, Drain/Spin, Starch, Express, Quickwash, Handwashable woollens, Silks

ADDITIONAL FUNCTIONS
Water plus, short, pre-wash, soak

SPIN
400–1400 rpm spin speeds
rinse hold & without spin

SAFETY FEATURES
Child resistant controls
water control system
check water inlet & drain indicators,
detergent overdosing indicator

CONSUMPTION
49 litre water, 1.02 kWh electricity

W 3364 Honeycomb Care Washing Machine

DESIGN
Straight fascia
Unique Miele Honeycomb Drum with
6 kg capacity
Extra large door opening
Direct enamel casing
H x W x D: 85 x 59.5 x 58 cm

CONTROLS
Single programme selector dial
programme sequence indicator
delay start with time left display
PC update facility

SPECIAL PROGRAMMES
Cottons, Minimum iron, Dark, Denims, Shirt, Delicates, Automatic, Separate rinse, Drain/Spin, Starch, Express, Quickwash, Handwashable woollens, Silks

ADDITIONAL FUNCTIONS
Water plus, short, pre-wash, soak

SPIN
400–1600 rpm spin speeds
rinse hold & without spin

SAFETY FEATURES
Child resistant controls
water control system
check water inlet & drain indicators,
detergent overdosing indicator

CONSUMPTION
49 litre water, 1.02 kWh electricity

W 3574 WPS "Allerwash" Honeycomb Care Washing Machine

DESIGN
Straight fascia
Unique Miele Honeycomb Drum with 6 kg capacity
Extra large door opening
Direct enamel casing
H x W x D: 85 x 59.5 x 58 cm

CONTROLS
Single programme selector dial
programme sequence indicator
time left display programme delay up to 24 hrs
PC update facility

SPECIAL PROGRAMMES
Cottons universal, Cottons Hygiene, Pillows Hygiene, Minimum iron, Dark, Denims, Shirt, Delicates, Automatic, Separate rinse, Drain/Spin, Starch, Express, Quickwash, Handwashable woollens, Silks, First wash

ADDITIONAL FUNCTIONS
Water plus, short, pre-wash, soak, intensive, rinse plus

SPIN
400–1600 rpm spin speeds
rinse hold & without spin

SAFETY FEATURES
Child resistant controls
water control system
check water inlet & drain indicators,
detergent overdosing indicator

CONSUMPTION
69 litre water, 1.14 kWh electricity

W 3985 WPS Navitronic Honeycomb Care Washing Machine

DESIGN
Angled fascia
Unique Miele Honeycomb Drum with 6 kg capacity
Extra large door opening
Large clear text display
Halogen drum lighting
Direct enamel casing
H x W x D: 85 x 59.5 x 58 cm

CONTROLS
Navitronic controls with "Jogshuttle"
programme sequence indicator
time left display programme delay up to 24 hrs
PC update facility

SPECIAL PROGRAMMES
Cottons universal, Cottons Hygiene, Minimum iron, Dark, Denims, Shirt, Delicates, Automatic, Separate rinse, Drain/Spin, Starch, Express, Quickwash, Handwashable woollens, Silks, Outer wear

ADDITIONAL FUNCTIONS
Water plus, short, pre-wash, soak, intensive,

SPIN
400–1800 rpm spin speeds
rinse hold & without spin

SAFETY FEATURES
Child resistant controls
water control system
check water inlet & drain indicators,
detergent overdosing indicator

CONSUMPTION
42 litre water, 0.85 kWh electricity

W 3923 WPS stainless steel

DESIGN
Angled fascia / LCD plus display
Unique Miele Honeycomb Drum with 6 kg capacity
Extra large door opening with LED lighting
H x W x D: 85 x 59.5 x 58 cm

CONTROLS
Single programme selector dial
programme sequence indicator
time left display programme delay up to 24 hrs

SPECIAL PROGRAMMES
Cottons, Minimum iron, Delicates, Silks, Woollens, Automatic, Shirts, Denim, Express, Hygiene, Starch, Spin, Dark garments, Curtains, Pillows, Sportswear, Outerwear, Proofing, Separate rinse

ADDITIONAL FUNCTIONS
Short, Pre-wash, Soak,Water plus, Rinse hold, Extra rinse

SPIN
Maximum spin speed 1600 rpm

SAFETY FEATURES
Child resistant controls
Waterproof system
In operation/system lock
detergent overdosing indicator

CONSUMPTION
47 litre water, 1.02 kWh electricity

WASHER AND DRYER STACKING KITS

Tumble-dryer	T 200/4000 series	T 200/4000/ 8000 series
WTV	WTV 406 LW [1]	WTV 407 LW [1]
Washing machine	W 500/3000 series with straight fascia	W 500/3000 series with angled fascia

T 7000 series	T 4000 "i" and decor models	T 200/4000/ 7000/8000 series
WTV 414 LW [1]	WTV 410 LW [2]	WTV 412 LW [3]
W 1000 series with	W 500/3000 series with straight fascia	W 500/3000 series with angled fascia

[1]) with pull-out shelf
[2]) stainless steel fascia available to co-ordinate stainless steel appliances
[3]) without pull-out shelf

T 7634 Novotronic Vented Tumble Dryer

DESIGN
Straight fascia
5 kg drum capacity
Extra large door opening
Enamel front with powder coated sides
H x W x D: 85 x 59.5 x 58 cm

CONTROLS
Single programme selector dial
programme sequence indicator
Delay start with time left display
PC update facility

SPECIAL PROGRAMMES
7 drying programmes including automtic, smoothing and woollens handcare

T 7644 C Novotronic Condenser Tumble Dryer

Same features as T 7634 vented dryer, but as condenser version

ENERGY EFFICIENCY B

T 4162 Honeycomb Care Vented Tumble Dryer

DESIGN
Straight fascia
6 kg honeycomb drum capacity
Extra large door opening
Enamel front with powder coated sides
H x W x D: 85 x 59.5 x 58 cm

CONTROLS
Single programme selector dial
programme sequence indicator
PC update facility

SPECIAL PROGRAMMES
7 sensor drying programmes including automatic, smoothing and woollens handcare

T 4262 C Honeycomb Care Condenser Tumble Dryer

Same features as T 4162 vented dryer, but as condenser version

ENERGY EFFICIENCY C

T 4462 C Honeycomb Care Condenser Tumble Dryer

DESIGN
Straight fascia
6 kg honeycomb drum capacity
Extra large door opening
Enamel front with powder coated sides
H x W x D: 85 x 59.5 x 58 cm

CONTROLS
Single programme selector dial
programme sequence indicator
programme delay up to 24 hrs
time left display
PC update facility
Air cooling system

SPECIAL PROGRAMMES
10 sensor drying programmes including automatic, shirts, denims, delicates, smoothing and woollens handcare

SAFETY FEATURES
Empty condenser water container indicator
Fully electronic child resistant controls
Electronic system lock

T 4464 C "Allerdry" Honeycomb Care Condenser Dryer

DESIGN
Straight fascia
6 kg Honeycomb drum capacity
Extra large door opening
Enamel front with powder coated sides
H x W x D: 85 x 59.5 x 58 cm

CONTROLS
Single programme selector dial with light ring
Programme sequence indicator
Programme delay up to 24 hrs
Time left display
PC update facility
Air cooling system

SPECIAL PROGRAMMES
10 sensor drying programmes including Allerdry cottons; minimum iron; pillows; timed drying hygiene smoothing and woollens handcare

SAFETY FEATURES
Empty condenser water container indicator light
Fully electronic child resistant controls
Clean out airways indicator light
Change filter indicator light
Electronic system lock

T 8623 C stainless steel condenser tumble dryer

DESIGN
Angled fascia with LCD plus display
6 kg Honeycomb drum with lighting
Extra large door opening
Enamel front with powder coated sides
H x W x D: 85 x 59.5 x 58 cm

CONTROLS
Single programme selector dial
Programme sequence indicator
Programme delay up to 24 hrs
Time left display
PC update facility
Air cooling system

SPECIAL PROGRAMMES
10 sensor drying programmes including Cottons, Minimum iron, Delicates, Automatic, Shirts, Denim, Woollens handcare, Silks handcare, Smoothing, Hygiene, Timed drying: Warm air, Cool air
Extra options: Low temperature, Short, Anti-crease Buzzer

SAFETY FEATURES
Empty condenser water container indicator light
Fully electronic child resistant controls
Clean out airways indicator light
Change filter indicator light
In operation/System lock

T 8685 C Navitronic Honeycomb Care Condenser Dryer

DESIGN
Angled fascia with aluminium look finish
6 kg Honeycomb drum capacity
Extra large door opening
Drum lighting
Enamel front with powder coated sides
H x W x D: 85 x 59.5 x 58 cm

CONTROLS
Jogshuttle control for programme selection plus shortcut buttons for favourites and extra options
Large clear text navigation display
Programme sequence indicator
Programme delay up to 24 hrs
Time left display
PC update facility
Air cooling system

SPECIAL PROGRAMMES
14 sensor drying programmes including Automatic; Outerwear; Denim and Shirts programmes;
Anti crease phase; woollens handcare and smoothing

SAFETY FEATURES
Empty condenser water container indicator
Fully electronic child resistant controls
Clean out airways indicator
Electronic system lock

WT 2670 Honeycomb Care Washer Dryer

DESIGN
Straight fascia
Unique Miele honeycomb drum with 5 kg wash capacity and 2.5 kg dry capacity
Extra large door opening
Direct enamel casing
H x W x D: 85 x 59.5 x 58 cm

CONTROLS
Single programme selector dial with light ring
Programme sequence indicator light
Programme delay up to 24 hrs
Time left display
PC update facility
Air cooling system
Unique load size indicator

SPECIAL PROGRAMMES
17 Wash Programmes and 14 sensor drying programmes including Sportswear; Reproofing and handcare woollens

SPIN SPEEDS
400–1600 rpm
rinse hold & without spin

SAFETY FEATURES
Empty condenser water container indicator
Fully electronic child resistant controls
Electronic system lock

B 890 Rotary Iron

DESIGN
Folds away for minimum storage space
85 cm wide heater plate
Free roller end

SAFETY FEATURES
Automatic finger guard

FEATURES
Aluminium heater plate
Three heater elements with special thermostat
Five choices of roller speed
Wide foot control bar

EASE OF USE
Laundry table to hold in soft folds
Easy to use controls
Comfortable working position with generous leg room

DIMENSIONS
H x W x D: 96 x 98.5 x 38 cm

B 895 Steam Rotary Iron
Same features as B 890, but with Steam function

Miele's unique cutlery tray and highly versatile baskets

Superior Dish and Glass care
• *Glasscare and intelligent sensor system*

G 975 PLUS Freestanding Dishwasher

DESIGN
60 cm wide model
Available in White only
H x W x D: 84.7–88.7 x 59.8 x 60 cm

CONTROLS
Fully electronic Novotronic controls
Single dial programme selection
PC update facility

PROGRAMME SELECTION
6 programmes: Intensive 75°C, Universal 55°C,
Universal Plus 55°C, Normal 50°C, Economy, Pre-Wash

CAPACITY
12 place setting

SOUND LEVEL
51 dB (A) re 1 pW in situ

CONSUMPTION
13 litre water and 1.05 kWh electricity in the Economy programme

SPECIAL FEATURES
Cutlery basket
Height adjustable upper basket
Versatile lower basket
Waterproof anti leak system

G 1040 Freestanding Dishwasher

DESIGN
60 cm wide model
Available in White only
H x W x D: 84.5–88 x 59.8 x 60 cm

CONTROLS
Fully electronic Novotronic controls
Single dial programme selection
PC update facility

PROGRAMME SELECTION
6 programmes: Quick wash 40°C, Light 50°C,
Sensor Wash 55–65°C, Energy Save, Pots & Pans 75°C, Pre-Wash

CAPACITY
12 place setting

SOUND LEVEL
48 dB (A) re 1 pW in situ

CONSUMPTION
13 litre water and 1.05 kWh electricity in the Economy programme

SPECIAL FEATURES
Cutlery basket
Height adjustable upper basket
Versatile lower basket
ECO Sensor
Waterproof anti leak system

G 1140 SC Freestanding Dishwasher

DESIGN
60 cm wide model
Available in White only
H x W x D: 84.5–88 x 59.8 x 60 cm

CONTROLS
Fully electronic controls
Touch button programme selection
PC update facility

PROGRAMME SELECTION
6 programmes: Quick wash 40°C, Light 50°C,
Sensor Wash 55–65°C, Energy Save, Pots & Pans 75°C, Pre-Wash

CAPACITY
12 place setting

SOUND LEVEL
48 dB (A) re 1 pW in situ

CONSUMPTION
13 litre water and 1.05 kWh electricity in the Economy programme

SPECIAL FEATURES
Unique Cutlery Tray
Height adjustable upper basket
Versatile lower basket
ECO Sensor
Waterproof anti leak system

G 1220 SC Freestanding Dishwasher

DESIGN
60 cm wide model
Available in White only
H x W x D: 84.5–88 x 59.8 x 60 cm

CONTROLS
Fully electronic controls
Touch button programme selection
PC update facility
Programme delay with time left display

PROGRAMME SELECTION
6 programmes: Quick wash 40°C, Sensor Wash, Sensor Wash Gentle, Energy Save, Pots & Pans 75°C, Pre-Wash

CAPACITY
12 place setting

SOUND LEVEL
48 dB (A) re 1 pW in situ

CONSUMPTION
13 litre water and 1.05 kWh electricity in the Economy programme

SPECIAL FEATURES
Unique Cutlery Tray
Height adjustable upper basket
Versatile lower basket
ECO Sensor
Waterproof anti leak system

G 1230 SC Freestanding Dishwasher

DESIGN
60 cm wide model
Available in Stainless Steel only
H x W x D: 84.5-88 x 59.8 x 60 cm

CONTROLS
Fully electronic controls
Touch button programme selection
PC Update facility
Programme delay with time left display

PROGRAMME SELECTION
6 programmes: Sensor wash, Quick wash 40°C, Sensor wash gentle, Energy save, Pots & pans 75°C, Pre-Wash

CAPACITY
12 place setting

SOUND LEVEL
48 dB (A) re 1 pW in situ

CONSUMPTION
13 litres water, 1.05 kWh electricity in Energy Save

SPECIAL FEATURES
Unique Cutlery Tray
Height adjustable upper basket
Versatile lower basket
ECO Sensor
Waterproof anti leak system

Miele's unique external steam generator

Simple and Efficient

DG 1050 Freestanding Steam Oven

DESIGN
Available in Stainless Steel only
Flush full-width tinted glazed door
20 litre stainless steel oven interior with 3 cooking levels
External steam generator
50 cm wide counter top model
H x W x D: 38.2 x 49.5 x 32.7 cm

OPERATING MODES
Cooking, reheating and defrosting by time and temperature
Time selectable from 1 min to 4 h 59 min
Temperatures adjustable between 40°C and 100°C in 5°C increments

ELECTRONIC CONTROLS
Electronic control dial with turn and press mechanism
Display for temperatures and time, descaling reminder and water level indication
Programmable cooking duration with automatic switch-off

SAFETY FEATURES
Enhanced vapour cooling and vented system door contact switch

ACCESSORIES
2 x 0.9 litre net capacity perforated stainless steel containers
Rack, drip tray, water tank with integrated heating element

M 8201 Freestanding Microwave Oven

DESIGN
Available in stainless steel only
26 litre stainless steel interior
H x W x D: 45 x 56 x 50 cm

FEATURES
Grill integrated into roof of cavity
Electronic timer and clock display
LED display for time of day and various functions
Rotary selector dial for microwave power, grill and combination programmes
Rotary selector dial for time and weight
Buttons for additional functions and automatic programmes
Interior light

OUTPUT
7 power levels: 80,150, 300, 450, 600, 750, 900 W
Grill output 800 W

FUNCTIONS
Quickstart with 30, 60, 120 seconds
Microwave and grill can be used individually or in combination
10 automatic programmes for defrosting, cooking and reheating
Timer 10 seconds to 90 minutes
Automatic warming function

DGGL 2 Steamer Insert

1.5 L Perforated stainless steel container

DGG 2 Steamer Insert

2.5 L Solid stainless steel container

DGG 3 Steamer Insert

4.0 L Solid stainless steel container

DGGL 4 Steamer Insert

4.0 L Perforated stainless steel container

DGGL 5 Steamer Insert

2.5 L Perforated stainless steel container

DGGL 6 Steamer Insert

4.0 L Perforated stainless steel container

DGG 7 Steamer Insert

4.0 L Solid stainless steel container

DGD Steamer Insert

Lid for solid stainless steel containers DGG 2 and DGG 7

CVA 2650 Freestanding NESPRESSO Coffee Machine

DESIGN
Available in Stainless Steel only
Black interior
Door hinged left
LED illumination of working area
50 cm wide freestanding counter top model
H x W x D: 37.2 x 49.5 x 32.4 cm

PREPARATION OPTIONS
Removable capsule magazine for 20 capsules of up to 5 different types
4 choices of cup size: Espresso, double espresso, coffee, double coffee
Water quantity can be programmed individually for each cup
Programme up to 4 additional user profiles to suit individual preferences

ELECTRONIC CONTROLS
2 graphic displays with clear text and up to 15 language options
2 rotary dials with turn and push function
Programmable on/off time

FEATURES
Automatic rinse and cleaning programme
Programmable water hardness setting
2 stainless steel through-flow water heaters
Cappuccinatore jug for frothing milk
1.5 litre capacity fresh water container
Large capacity waste container for 25 spent capsules
Safety lock
Refill reminder for: Capsules, Fresh water, Descaling programme, empty drip tray, empty capsule container

CVC 26 Cappuccinatore

Cappucinatore - A system designed for perfectly frothed milk
Froth milk in the jug or dispense frothed milk simultaneously straight into the cup
Dishwasher safe

GCEO insert

Dishwasher insert for cappuccinatore jug

Miele's Wine Cellar has an electronic temperature regulation between 5°C and 22°C to prevent temperature fluctuations

Dynamic Cooling system to create a constant humidity level

Charcoal filter to prevent the wine from external odours

K 8852 SD Refrigerator

DESIGN
Free standing model
Door hinged right, convertible
Softline door with aluminium coloured lever handle
Super cool button with indicator light
H x W x D: 184.1 x 60 x 63.2 cm

CAPACITY
Larder refrigerator with 398 l/ 14.1 cu ft usable space
Automatic defrosting
Dynamic cooling
Interior light with temperature regulator
8 high quality glass shelves, including 1 split shelf, 6 are height adjustable
4 fruit and vegetable compartments
Chrome bottle rack

DOOR INTERIOR
Dairy compartment
3 half racks, 2 bottle racks

FN 4857 S Frost Free Freezer

DESIGN
Free standing model
Door hinged left, convertible
Softline door with aluminium coloured lever handle
Super Freeze button with indicator light
H x W x D: 184.1 x 60 x 63.2 cm

CAPACITY
4 star freezer with 257 l/ 9.1 cu ft usable space
Frost free system with Automatic defrost
Freezes 18 kg in 24 hrs
Digital temperature display with selector buttons
7 +1 non-tip sealed transparent drawers
Removable glass cold plate between drawers
2 cool packs, ice cube tray
Freezer tray
Frozen food marker system

KFN 8452 SD Frost Free Fridge Freezer

DESIGN
Free standing model
Doors hinged right, convertible
Softline doors with aluminium coloured lever handle
Super freeze switch with indicator light
H x W x D: 180.6 x 60 x 63.2 cm

CAPACITY
Total capacity: 313 l/11.1 cu ft usable space
Fridge capacity: 224 l/8 cu ft usable space
Freezer capacity: 89 l/3.1 cu ft usable space

REFRIGERATOR
Automatic defrosting
Dynamic cooling
Interior light with temperature regulator
Fully enclosed evaporator
4 high quality glass shelves, including 1 split shelf, 3 are height adjustable
2 fruit and vegetable compartments
Versatile door fittings with bottle rack and covered dairy compartment

4-STAR FREEZER
Frost Free system with automatic defrost
3 large non-tip sealed transparent drawers
Removable cold plate between 2 drawers
frozen food marker system
2 cool packs, ice cube tray
Freezes 14 kg in 24 hrs

KTN 4352 SD ED Frost Free Fridge Freezer

DESIGN
Free standing model
Door hinged right, convertible
Stainless steel front with “soft close” metal lever handle
Super freeze switch with indicator light
H x W x D: 169 x 60 x 63 cm

CAPACITY
Total capacity: 284 l/10 cu ft usable space
Fridge capacity: 224 l/7.9 cu ft usable space
Freezer capacity: 60 l/2.1 cu ft usable space

REFRIGERATOR
Automatic defrosting
Dynamic cooling
Interior light with temperature regulator
Fully enclosed evaporator
5 high quality glass shelves, including 1 split shelf, 4 are height adjustable
2 fruit and vegetable compartments
Versatile door fittings with bottle rack and covered dairy compartment

4-STAR FREEZER
Frost Free system with automatic defrost
Height adjustable rack
ice cube tray
Freezes 7 kg in 24 hrs

KF 8582 SD ED Fridge Freezer

DESIGN
Free standing model
Doors hinged right, convertible
Stainless steel front with soft close metal handle
Super freeze switch with indicator light
H x W x D: 184 x 75 x 63 cm

CAPACITY
Total capacity: 432 l/15.2 cu ft usable space
Fridge capacity: 337 l/11.9 cu ft usable space
Freezer capacity: 95 l/3.3 cu ft usable space

REFRIGERATOR
Automatic defrosting
Dynamic cooling
Interior light with temperature regulator
Fully enclosed evaporator
4 high quality glass shelves, including 1 split shelf, 3 are height adjustable
3 wire bottle racks
2 fruit and vegetable compartments
Versatile door fittings with bottle rack and covered dairy compartment

4-STAR FREEZER
2 large non-tip sealed transparent drawers
ice cube tray
Freezes 8 kg in 24 hrs

KFN 8562 SD ED Frost Free Fridge Freezer

DESIGN
Free standing model
Doors hinged right, convertible
Stainless steel front with “soft close” metal lever handle
Super freeze switch with indicator light
H x W x D: 180.6 x 60 x 63.2 cm

CAPACITY
Total capacity: 313 l/11.1 cu ft usable space
Fridge capacity: 224 l/8 cu ft usable space
Freezer capacity: 89 l/3.1 cu ft usable space

REFRIGERATOR
Automatic defrosting
Dynamic cooling
Interior light with temperature regulator
Fully enclosed evaporator
4 high quality glass shelves, including 1 split shelf, 3 are height adjustable
2 fruit and vegetable compartments
Versatile door fittings with bottle rack and covered dairy compartment

4-STAR FREEZER
Frost Free system with automatic defrost
3 large non-tip sealed transparent drawers
Removable cold plate between 2 drawers
frozen food marker system
2 cool packs, ice cube tray
Freezes 14 kg in 24 hrs

K 8952 SD ED Refrigerator

DESIGN
Free standing model
Doors hinged right, convertible
Stainless steel front with soft close metal handle
Super freeze switch with indicator light
H x W x D: 184.1 x 60 x 63.2 cm

CAPACITY
Larder refrigerator with 398 l/14.1 cu ft usable space

REFRIGERATOR
Automatic defrosting
Dynamic cooling
Interior light with temperature regulator
Fully enclosed evaporator
7 high quality glass shelves, including 1 split shelf, 6 are height adjustable
Chrome bottle rack
4 fruit and vegetable compartments

DOOR INTERIOR
Versatile door fittings with 2 bottle racks, 3 half racks and dairy compartment

FN 4957 SED Frost Free Freezer

DESIGN
Free standing model
Door hinged left, convertible
Stainless steel front with soft close metal lever handle
Super Freeze button with indicator light
H x W x D: 184.1 x 60 x 63.2 cm

CAPACITY
4 star freezer with 257 l/9.1 cu ft usable space
Frost free system with Automatic defrost
Freezes 18 kg in 24 hrs
Digital temperature display with selector buttons
7 +1 non-tip sealed transparent drawers
Removable glass cold plate between drawers
2 cool packs, ice cube tray
Freezer tray
Frozen food marker system

KFN 8701 SE ED Frost Free Freezer with StayFresh

DESIGN
Free standing model
Doors hinged left, convertible
Stainless steel front with soft close metal handle
Super freeze switch with indicator light
Super cool button with indicator light
H x W x D: 184.1 x 60 x 63.2 cm

CAPACITY
Total capacity: 249 l/8.8 cu ft usable space
StayFresh zone capacity: 130 l/4.6 cu ft usable space
Freezer capacity: 119 l/4.2 cu ft usable space

STAYFRESH ZONE
Automatic defrosting
Interior light with temperature regulator
Fully enclosed evaporator
2 high quality glass shelves
Chrome bottle rack
1 dry and 1 humidity controlled Stayfresh compartment
Versatile door fittings with bottle rack and covered dairy compartment

4-STAR FREEZER
2 small non-tip sealed transparent drawers
3 large non-tip sealed transparent drawers
Removable glass cold plate between drawers
2 cool packs,ice cube tray
Frozen food marker system
Freezes 14 kg in 24 hrs

KWFN 8706 SE ED Freezer with Wine Cooler

DESIGN
Free standing model
Doors hinged left convertible
Stainless steel front with soft close metal handle
Super freeze switch with indicator light
H x W x D: 184.1 x 60 x 63.2 cm

CAPACITY
Total capacity: 263 l/9.3 cu ft usable space
Wine Cooler Capacity: 114 l/5.1 cu ft usable space
Freezer capacity: 119 l/4.2 cu ft usable space

WINE COOLER
Frost free system with automatic defrosting
Dynamic cooling/humidity button with indicator light
5 removable wooden shelves with decor strips for 40 bottles
Charcoal filter

4-STAR FREEZER
Frost free system with automatic defrost
2 small non-tip sealed transparent drawers
3 large non-tip sealed transparent drawers
Removable glass cold plate between drawers
2 cool packs
ice cube maker (1.1 kg in 24 hrs)
Frozen food marker system
Freezes 14 kg in 24 hrs

KWL 4712 SG ED Wine Storage Unit

DESIGN
Freestanding model
Doors hinged right, convertible
Stainless steel casing with full height glass door
Light grey inner cabinet
Interior lighting
H x W x D: 165.8 x 66 x 68.3 cm

CAPACITY
Total Capacity: 162 bottles (0.75 l Bordeaux)

WINE COOLER
Electronic soft touch controls concealed behind the door
Temperature regulation from +5°C to + 22°C using +/- controls
Digital temperature display
Dynamic cooling
Audible warning tone with OFF button
6 storage levels including 5 height adjustable acacia wood shelves
Fresh air intake via an active charcoal filter
Cabinet heater for low ambient temperatures
Constant humidity levels up to 70%
Door lock

KWT 4974 SG ED Wine Conditioning Unit

DESIGN
Freestanding model
Doors hinged right, convertible
Stainless steel casing with full height glass door
Light grey inner cabinet
Interior lighting
H x W x D: 185.5 x 66 x 67.4 cm

CAPACITY
Total Capacity: 162 bottles (0.75 l Bordeaux)
– 36 in the upper zone, 45 in the middle zone and 62 in the lower zone

WINE COOLER
Electronic soft touch controls concealed behind the door
Temperature regulation from +3°C to 20°C using +/- controls
Digital temperature display
Dynamic cooling
Audible warning tone with OFF button
13 storage levels including 5 height adjustable acacia wood shelves
2 in the upper zone, 3 in the middle zone and 5 in the lower zone
Fresh air intake via an active charcoal filter
Cabinet heater for low ambient temperatures
Constant humidity levels up to 70%
Door lock

KFN 8996 SDE ED-1 Frost Free Fridge Freezer

DESIGN
Free standing model
Doors hinged right, convertible
Stainless steel front with soft close metal handle
Super freeze switch with indicator light
Super cool button with indicator light
Two independently controlled compressors
H x W x D: 200 x 75 x 63 cm

CAPACITY
Total capacity: 439 l/15.5 cu ft usable space
Fridge capacity: 320 l/11.3 cu ft usable space
Freezer capacity: 119 l/4.2 cu ft usable space

REFRIGERATOR
Dynamic cooling
Automatic defrosting
Interior LED lighting illuminating glass shelves and door shelves
Fully enclosed evaporator
5 high quality glass shelves including 1 split shelf, 4 are height adjustable
Chrome bottle rack
1 fruit and vegetable compartment
Versatile door fittings with bottle rack, 2 half racks and covered dairy compartment

4-STAR FREEZER
Frost free system with automatic defrosting
2 small non-tip sealed transparent drawers
2 large non-tip sealed transparent drawers
Removable glass cold plate between drawers
2 cool packs
Ice cube maker (1.1 kg/24 hrs)
Frozen food marker system
Freezes 10 kg in 24 hrs

KFNS 3929 SDEed American Style Fridge Freezer

DESIGN
American Style – Free standing model with Stainless steel casing
Three independently controlled compressors (Wine/Fridge/Freezer)
H x W x D: 187 x 121 x 68.4 cm

CAPACITY
Total capacity: 600 l/21.2 cu ft usable space
Fridge capacity: 237 l/11.3 cu ft usable space
StayFresh zone capacity: 100 l/3.5 cu ft usable space
Wine cellar capacity: 144 l/5.1 cu ft usable space
Freezer capacity: 119 l/4.2 cu ft usable space
Wine storage/Freezer with two independently controlled compressors on left hand side

REFRIGERATOR
Automatic defrosting
Fully enclosed evaporator
5 high quality glass shelves including 1 split shelf, 4 are height adjustable
2 fruit and vegetable compartment
Versatile door fittings with bottle rack, 2 half racks and covered dairy compartment
Interior light

STAYFRESH ZONE
1 dry StayFresh compartment with up to 45% humidity
2 humidity controlled StayFresh compartments, can be regulated between 45% and 90% humidity

WINE CELLAR
Frost free system with automatic defrosting
5 shelves for 40 bottles, charcoal filter

4-STAR FREEZER
Frost free system with automatic defrosting
2 small non-tip sealed transparent drawers
2 large non-tip sealed transparent drawers
Removable glass cold plate between drawers
Ice cube maker (1.1 kg/24 hrs)
Freezes 10 kg in 24 hrs

Convenient and Compact Design
Flexible Maneuverability
Miele

S 4211 – Lemon Yellow

Designed and tested for an average life of 20 years

CONTROLS
Electronic suction power regulation using rotary dial
6 power settings including economy setting

PERFORMANCE
2000 W motor – powerful but quiet

FILTER SYSTEM
Super Air Clean filter
3.5 litre self-sealing dustbag – Type F/J/M

FEATURES
Stainless steel height adjustable telescopic suction tube
Standard floorhead SBD 450-3 with 360 comfort swivel joint
Operating radius 9 m
3 smooth running 360 castor wheels
Park system for floorhead at rear of cleaner
Storage system at either side for easy carrying
Automatic cable rewind

SAFETY
Bumper strip to protect cleaner and furniture
Change dustbag indicator
Automatic cut-out on overheating

S 4211 Parquet & Co – Electric Blue Metallic

Designed and tested for an average life of 20 years

CONTROLS
Electronic suction power regulation using rotary dial
6 power settings including economy setting

PERFORMANCE
2000 W motor – powerful but quiet

FILTER SYSTEM
Super Air Clean filter
3.5 litre self-sealing dustbag – Type F/J/M

FEATURES
Stainless steel height adjustable triscopic suction tube
Standard floorhead SBD 450-3 with 360 comfort swivel joint
Parquet brush SBB Parquet-3
Operating radius 9 m
3 smooth running 360 castor wheels
Park system for floorhead at rear of cleaner
Storage system at either side for easy carrying
Automatic cable rewind

SAFETY
Bumper strip to protect cleaner and furniture
Change dustbag indicator
Automatic cut-out on overheating

S 5210 – Deep Black

Designed and tested for an average life of 20 years

CONTROLS
Electronic suction power regulation using rotary dial
6 power settings including "Silence" setting

PERFORMANCE
2200 W motor – powerful but quiet

FILTER SYSTEM
Super Air Clean filter
4.5 litre self-sealing dustbag – Type GN

FEATURES
Stainless steel height adjustable telescopic suction tube
Standard floorhead SBD 285-3 with retractable brushes for edge to edge cleaning of carpets and hard floors and 360 comfort swivel joint
Operating radius 10 m
Park system for floorhead at rear of cleaner
Storage system at either side for easy carrying
Automatic cable rewind with comfort touch

SAFETY
Bumper strip to protect cleaner and furniture
Change dustbag indicator
Automatic cut-out on overheating

S 5280 – Silver Metallic

Designed and tested for an average life of 20 years

CONTROLS
Electronic suction power regulation using rotary dial
6 power settings including "Silence" setting

PERFORMANCE
2200 W motor – powerful but quiet

FILTER SYSTEM
Active HEPA filter
4.5 litre self-sealing dustbag – Type GN

FEATURES
Stainless steel height adjustable telescopic suction tube
Standard floorhead SBD 285-3 with retractable brushes for edge to edge cleaning of carpets and hard floors and 360 comfort swivel joint
Operating radius 10 m
Park system for floorhead at rear of cleaner
Storage system at either side for easy carrying
Automatic cable rewind with comfort touch

SAFETY
Bumper strip to protect cleaner and furniture
Change dustbag indicator
Automatic cut-out on overheating

S 5360 Cat & Dog 2200 – Titan Red Metallic

Designed and tested for an average life of 20 years

CONTROLS
Electronic suction power regulation using rotary dial
6 power settings including "Silence" setting

PERFORMANCE
2200 W motor – powerful but quiet

FILTER SYSTEM
Active Air Clean filter
4.5 litre self-sealing dustbag – Type GN

FEATURES
Stainless steel height adjustable telescopic suction tube
Standard floorhead SBD 550-3 with retractable brushes for edge to edge cleaning of carpets and hard floors and 360 comfort swivel joint
Full size Turbobrush STB 205-3
Socket for Miele Electrobrush
Operating radius 10 m
Park system for floorhead at rear of cleaner with automatic on/off switch
Storage system at either side for easy carrying
Automatic cable rewind with comfort touch

SAFETY
Bumper strip to protect cleaner and furniture
Change dustbag indicator
Automatic cut-out on overheating with indicator light

S 5380 Solution HEPA 5000 – Marine Blue Velvet

Designed and tested for an average life of 20 years

CONTROLS
Electronic suction power regulation using rotary dial
6 power settings including "Silence" setting

PERFORMANCE
2200 W motor – powerful but quiet

FILTER SYSTEM
Active HEPA filter
4.5 litre self-sealing dustbag – Type GN

FEATURES
Stainless steel height adjustable telescopic suction tube
Standard floorhead SBD 550-3 with retractable brushes for edge to edge cleaning of carpets and hard floors and 360 comfort swivel joint
Parquet brush SBB 300-3
Full size Turbobrush STB 205-3
Socket for Miele Electrobrush
Operating radius 10 m
Park system for floorhead at rear of cleaner with automatic on/off switch
Storage system at either side for easy carrying
Automatic cable rewind with comfort touch

SAFETY
Bumper strip to protect cleaner and furniture
Change dustbag indicator
Automatic cut-out on overheating with indicator light

STB 205 Turbobrush

- Rotating roller brush
- Buffer strip around the turbobrush protects furniture from scuffing

STB 101 Mini Turbobrush

- For vacuuming cut pile stair carpets and removing dust and pet hairs from upholstery

MicroSet SMC 10

- Designed for fiddly nooks and crannies such as PC keybords, stereo equipment, intricately carved furniture and ornaments

CarClean Set SSC Vario

- Extra long crevice noozle (30 cm) for getting between the seats and inside compartments

SBB 300-3 Parkett

- New Parquet brush, which has a 90° rotational action enabling easy access around obstacles such as table legs, etc.

Floorbrush SBB Parkett

- Specially designed for parquet, floorboards and tiled floors

Dust bags F/J/M Plus
For models S 300/500/700/4000

- 5 dust bags in a box and contains a super air clean filter and a dust compartment filter

Dustbags G/N Plus
For models S 400/600/800/5000

- 5 dust bags in a box and contains a super air clean filter and a dust compartment filter

SMD 10 Mattress Nozzle

- Ideally suited to reaching between the mattress and the bedstead or between the cushions of upholstered furniture

SEB 216-2 Electrobrush

- Recommended for thorough cleaning of carpets subjected to heavy use and likely to suffer from trod
- Electrically driven with own motor, ensures constant brush rotation

Active Hepa Filter

- Conforms to European standard EN 1822
- Trapping particles as small as 0.3 of a micron (i.e. particles such as dust mite faeces and tobacco smoke)
- Hold advantages of charcoal filter
- Designed and tested for 50 working hours or 12 months

Active Air Clean Filter

- Combination of the super air clean filter with an active charcoal filter
- Absorbs odours from the dust bag – especially useful for families wit pets
- Designed and tested for 50 working hours or 12 months

Model no.		W 1513	W 526	W 3240	W 3364	W 3574 WPS	W 3923 WPS	W 3985	WT 2670
Features									
Unique Miele Honeycomb drum		–	–	•	•	•	•	•	•
Controls									
Fully Electronic Novotronic / Navitronic Controls		–	–	•/–	•/–	•/–	•/–	– /•	•
Sensor load size indicator		–	–	–	–	–	–	•	•
Automatic detergent dose recommendation		–	–	–	•	–	–	•	•
Spin Speed (Maximum)		1300	1400	1400	1600	1600	1600	1800	1600
Program sequence LEDs		–	6	6	6	7	•	Display	Display [2])
Dimensions and Weight									
Capacity – washing	kg	5	5	6	6	6	6	6	5
Capacity – drying	kg	–	–	–	–	–	–	–	2.5
Height	cm	85	85	85	85	85	85	85	85
Width	cm	59.5	59.5	59.5	59.5	59.5	59.9	59.5	59.5
Depth (including distance from wall) / with door open	cm	63.4/107.4	58/97.5	58/97.5	58/97.5	58/97.5	58/97.5	58	60/97
Weight	kg	99	93	95	94	94	94	94	99
Stacked height (with matching dryer)	cm	170/172	170/172	170/172	170/172	170/172	169/170	170/172	–
Performance / Consumption data [1])									
Water consumption	liters	45	45	49	49	69	47	47	56+9 [3])
Electricity consumption	kWh	0.85	0.85	1.02	0.85	1.14	1.02	1.02	2.4 [3])
Standard programme duration [4])	min	109/59	116/59	109/59	109/59	127/58	116/59	109/59	160 [5])
Residual moisture level		50%	50%	50%	44%	44%	44%	43%	44%
Electricity and Water Connections									
Fuse rating / Total rated load	A / kW	13/ –	13/2.4	13/2.4	13/ –	13/2.4	13/2.4	13/2.4	13/2.7
Water inlet hose	m	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6
Drain connection hose	m	1.5	1.5	1.5	1.5	1.5	1.5	1.5	1.5

• = yes, existing
[1]) According to EN 60456 tested in Cottons 60°C Intensive with a 5 kg load
[2]) Including drying process
[3]) Washing & drying cycle – According to EN 60456 and EN 61121 tested in Cottons 60°C and Cottons Normal (washload 5 kg, dryload 2.5 kg)
[4]) Cottons 60°C Normal, 5 kg load / Delicates 30°C Normal, 1 kg load
[5]) Washing & drying 2.5 kg

Model no.		T 7634C	T 4162	T 4262 C	T 4462 C	T 4464 C	T 8623 C	T 8685C
Features								
Unique Miele Honeycomb drum		–	•	•	•	•	•	•
Fuzzy logic sensitive drying system		•	•	•	•	•	•	•
Automatic moisture sensor drying		•	•	•	•	•	•	•
Easy Clean fluff filter		•	•	•	•	•	•	•
Controls								
Fully Electronic Novotronic / Navitronic Controls		•/–	•/–	•/–	•/–	•/–	•/–	–/•
"Favourites" – memory and shortcut buttons		•/•	–	–	–	–	–	•
Dimensions and Weight								
Capacity	kg	6	6	6	6	6	6	6
Height	cm	85	85	85	85	85	85	85
Width	cm	59.5	59.5	59.5	59.5	59.5	59.9	59.5
Depth (including distance from wall) / with door open	cm	63.4/107.4	58/106	58/106	58/106	58/106	58/106	58/106
Weight	kg	46	48	54	54	54	54	54
Stacked height (with matching washing machine)	cm	170/172	170/172	170/172	170/172	170/172	170/172	170/172
Electrical connection								
Fuse rating / Total rated load	A / kW	13/–	13/2.7	13/2.85	13/2.85	13/2.85	13/–	13/–
Drain connection	m	–	–	2	2	2	1.5	1.5
Maximuum drain pump height / length	m	–	–	1/3	1/3	1/3	4	1.5/4
Performance / Consumption data [1])								
Electricity consumption	kWh	2.75	2.9	3.05	2.9	2.95	2.85	2.85
Programme duration	min	68	81	91	83	83	78	78

• = yes, existing

[1]) For Cotton Normal spun at 1400 rpm (50% residual)

Model no.		G 975	G 1040	G 1140SC	G 1220 SC	G 1230 SC
Design						
Width	cm	60	60	60	60	60
Freestanding		•	•	•	•	•
Colours		white	white	white	white	stainless steel
Controls						
Fully Electronic Novotronic controls		•	•	•	•	•
Single Dial Control / Button touch controls		•/–	•/–	–/•	–/•	–/•
Delay Start		–	–	–	•	•
Maximum sound level (re 1pW)		51 dB	48 dB	48 dB	48 dB	48 dB
Consumption data [1]) for Economy / Normal 50°C						
Energy efficiency class [2])		A	A	A	A	A
Wash performance class [2])		A	A	A	A	A
Drying performance class [2])		A	A	A	A	A
Water consumption	liters	13	13/13–22	13/13–22	13/13–22	13/13–22
Energy consumption	kWh	1.05	1.05/1–1.4	1.05/1–1.4	1.05/1–1.4	1.05/1–1.4
Program duration	min	168	176/105–145	176/105–145	176/85–142	176/85–142
Programs		6	6	6	6	6
Features						
Turbothermic plus drying		•	–	•	•	•
Triple filter system		•	•	•	•	•
ECO Sensor / Auto Sensor		–	•/–	•/–	–/•	–/•
Capacity						
International place settings		12	12	12	12	12
Plate diameter, upper basket		15–19	23	15–19	15–19	15–19
Plate diameter, lower basket		26–30	28	26–30	27–31	27–31
Installation						
Height (adjustable)	cm	84.7–88.7	84.5–88.0	84.5–88.0	84.5–88.0	84.5–88.0
Width	cm	59.8	59.8	59.8	59.8	59.8
Depth	cm	60	60	60	60	60
Weight	kg	60	59	59	59	59
Fuse rating / Total rated load	A / kW	230 V to 240 V, 50 Hz. fuse rating 13 A				
Water connection		1.5 m waterproof double hose with 19 mm (3/4 inch) threaded union				
Water supply		Cold or hot. max 60°C; 0.3 to 10 bar (30 to 1000 kPa)				
Drain connection		1.5 m flexible drain hose, internal diameter 22 mm (7/8 inch)				
Maximum drain pump height/length		1 m/4 m	1 m/4 m	1 m/4 m	1 m/4 m	1 m/4 m

• = yes, existing
[1]) Connected to 15°C cold water supply
[2]) According to EN 50242 using standard program Economy

Model no.		DG 1050
Design		
Door hinged right/left		–/•
Dimensions and weight		
Height	cm	38.2
Width	cm	49.5
Depth	cm	32.7
Weight	kg	19.3
Features		
Shelf levels		3
Cooking containers		2
Water container		1
Permanent water connection		–
Controls		
IC display / with clear text		•/•
Rotary switches		1
Cooking functions		
Cooking settings		–
Temperature control	°C	40–100
Programmable cooking times		•
Electrical connection		
Fuse rating / Total rated load	A / kW	13/2.2

Model no.		CVA 2650
Design		
Door hinged right/left		–/•
Dimensions and weight		
Height	cm	38.0
Width	cm	49.
Depth	cm	34.0
Weight	kg	25.0
Features		
Freshwater container	l	1.5
Steam spout / Milk frother		•
Water container		•
Capsule container		•
Controls		
Programmable water quantity per cup	ml	30–175
LC display / with clear text		•/•
Rotary switches		2
Language programmable		•
Stand-by function with timer		•
Indicators		•
Electrical connection		
Fuse rating / Total rated load	A / kW	13/2.3

Model no.		M 8201
Aplliances Dimension		
Height	cm	30.5
Width	cm	52
Depth	cm	42.2
Volume	l	26
Buildings in dimension		
Height	cm	20.7
Width	cm	34.2
Depth	cm	36.8
Weight	kg	16.5
Specifications		
no. of power levels		
Power output levels	W	80/150/300/ 450/600/ 750/900
Browning element	W	800
No. of automatic		10 s–90 min
Electrical connection		
Fuse rating / Total rated load	A / kW	13/2.05

Model no.		K 8852 SD	K 8952 SDed–1	FN 4857 S	FN 4957 Sed–1	KFN 8452 SD
Type of appliance						
Freestanding		•	•	•	•	•
Door hinged r = right, c = convertible, l = left		r/c	r/c	l/c	l/c	r/c
Compressors*		1	1	1	1	1
Star marking [1])			****	****	****	****
Type of climate [2])		SN–T	SN–T	SN–T	SN–T	SN–T
Dimensions and weight						
Height	cm	184.1	184.1	184.1	184.1	180.6
Width	cm	60	60	60	60	60
Depth inc distance from the wall [3])	cm^3	63.2	63.2	63.2	63.2	63.2
Net weight	kg	79.7	78.9	80.5	78.4	77.5
Capacities						
Net fridge capacity	litres/cu ft	398/14.1	398/14.1	–	–	224/7.9
Net stay fresh capacity	litres/cu ft	–	–	–	–	–
Net freezer capacity	litres/cu ft	–	–	257/9.1	257/9.1	89/3.1
Net wine cooler capacity	litres/cu ft	–	–	–	–	–
Defrosting procedure						
Fridge		Automatic	Automatic	–	–	Automatic
Freezer		–	–	Automatic	Automatic	Automatic
Electrical connection						
Fuse rating / Total rated load	A / kW	13/0.13	13/0.13	13/0.259	13/0.259	13/0.13
Energy consumption [4])						
Per year		182.5	183	328.5	328.5	376
Energy efficiency rating		A	A	A	A	A
Complies with safety regulations		•	•	•	•	•

• = yes, existing

[1]) **** = frozen food storage compartment with -18°C

[2]) SN = suitable for normal climate with surrounding temperatures of 10°C to 32°C
N = suitable for surrounding temperatures of 16°C to 32°C
SN–T = suitable for surrounding temperatures of 10°C to 43°C
SN–ST = suitable for surrounding temperatures or 10°C to 38°C

[3]) Depth includes the curve on the door on freestanding softline models

[4]) Energy consumption per year was calculated according to DIN EN 153 1990. Tests were made on a 220 V/50 Hz appliance.

Model no.		KTN 4352 Sded	KF 8582 Sded	KFN 8562 SD ED	KFN 8701 SEed–1	KWFN 8706 SEed–1
Type of appliance						
Freestanding		•	•	•	•	•
Door hinged r = right, c = convertible, l = left		r/c	r/c		l/c	l/c
Compressors*		1	1	1	2	2
Star marking [1])		****	****	****	****	****
Type of climate [2])		SN–T	SN–T	SN–T	SN–T	SN–T
Dimensions and weight						
Height	cm	169	184	184	184.1	184.1
Width	cm	60	75	60	60	60
Depth inc distance from the wall [3])	cm^3	63	63	63.2	63.2	63.2
Net weight	kg	74	102		92.9	87.9
Capacities						
Net fridge capacity	litres/cu ft	224/7.9	337/11.9	224/7.9	–	–
Net stay fresh capacity	litres/cu ft	–	–	–	130/4.5	–
Net freezer capacity	litres/cu ft	60/2.1	95/3.3	89/3.1	119/4.1	119/4.1
Net wine cooler capacity	litres/cu ft	–	–	–	–	144/5.0
Defrosting procedure						
Fridge		Automatic	Automatic	Automatic	Automatic	Automatic
Freezer		Automatic	Manual	Automatic	Automatic	Automatic
Electrical connection						
Fuse rating / Total rated load	A / kW	13/0.14	13/0.14	13/0.13	13/0.17	13/0.17
Energy consumption [4])						
Per year		328.5	321	376	379.6	343.1
Energy efficiency rating		A	A+	A	A	A
Complies with safety regulations		•	•	•	•	•

• = yes, existing

[1]) **** = frozen food storage compartment with -18°C

[2]) SN = suitable for normal climate with surrounding temperatures of 10°C to 32°C
N = suitable for surrounding temperatures of 16°C to 32°C
SN–T = suitable for surrounding temperatures of 10°C to 43°C
SN–ST = suitable for surrounding temperatures or 10°C to 38°C

[3]) Depth includes the curve on the door on freestanding softline models

[4]) Energy consumption per year was calculated according to DIN EN 153 1990. Tests were made on a 220 V/50 Hz appliance.

Model no.		KWL 4712 SGed	KWT 4974 SGed	KWFN 8996 SDEed–1	KFNS 3929 Sed
Type of appliance					
Freestanding		•	•	•	•
Door hinged r = right, c = convertible, l = left		r/c	r/c	r/c	–
Compressors*		1	1	2	3
Star marking [1])				****	****
Type of climate [2])		SN–ST	SN–ST	SN–T	SN–T
Dimensions and weight					
Height	cm	165.8	185.5	200	187
Width	cm	66	66	75	121
Depth inc distance from the wall [3])	cm^3	68.3	67.4	63	68.4
Net weight	kg	82	97	115	–
Capacities					
Net fridge capacity	litres/cu ft	–	–	320/11.3	237/11.9
Net stay fresh capacity	litres/cu ft	–	–	–	100/3.5
Net freezer capacity	litres/cu ft	–	–	119/4.2	119/4.2
Net wine cooler capacity	litres/cu ft	386/13.6	386/13.6	–	144/5.1
Defrosting procedure					
Fridge		Automatic	Automatic	Automatic	Automatic
Freezer		–	–	Automatic	Automatic
Electrical connection					
Fuse rating / Total rated load	A / kW	13/0.12	13/0.12	13/0.23	13 x 2 / 0.13 + 0.17
Energy consumption [4])					
Per year		178	332	464	533
Energy efficiency rating		–	–	A	A
Complies with safety regulations		•	•	•	•

• = yes, existing

[1]) **** = frozen food storage compartment with -18°C

[2]) SN = suitable for normal climate with surrounding temperatures of 10°C to 32°C
N = suitable for surrounding temperatures of 16°C to 32°C
SN–T = suitable for surrounding temperatures of 10°C to 43°C
SN–ST = suitable for surrounding temperatures or 10°C to 38°C

[3]) Depth includes the curve on the door on freestanding softline models

[4]) Energy consumption per year was calculated according to DIN EN 153 1990. Tests were made on a 220 V/50 Hz appliance.

Model no.		S 4211	S 4211 Parquet & Co	S 5210	S 5280	S 5360	S 5380
Features & Equipment							
Colour		Lemon Yellow	Electric Blue Metallic	Deep Black	Silver Metallic	Titan Red Metallic	Marine Blue Velvet
Controls		Rotary Dial	Rotary Dial	Rotary Dial	Rotary Dial	Rotary Dial	Rotary Dial
Operating radius	m	9	9	10	10	10	10
Usable dust bag volume	l	3.5	3.5	4.5	4.5	4.5	4.5
Suction power control: Electronic / via ir vent		•/–	•/–	•/–	•/–	•/–	•/–
Dust bag change indicator		•	•	•	•	•	•
Sound insulation: Standard / Silence		•/–	•/–	•/•	•/•	•/•	•/•
Intensive Clean dust bag type		F/J/M Plus	F/J/M Plus	GN–2	GN–2	GN–2	GN–2
Super AirClean filter		•	•	•	–	–	–
Active AirClean filter		–	–	–	–	•	–
Active HEPA filter		–	–	–	•	–	•
"Change filter" indicator		–	–	–	–	–	–
Thermal safety cut-out indicator		•	•	•	•	•	•
Park system on / off		–	–	–	–	–	•
Cable rewind: Manual / Auto remove		•/–	•/–	–/•	–/•	–/•	–/•
Socket for Electro Brush SEB 216-2		–	–	–	–	–	•
Hose coupling shutter		–	–	–	–	•	–
Accessories supplied as standard							
Stainless steel suction tube [1])		b	c	b	b	b	b
Smooth running floor head		SBD 450–3	SBD 450–3	SBD 285–3	SBD 285–3	SBD 550–3	SBD 550–3
Allergotec floor head		–	–	–	–	–	–
Turbo brush		–	–	–	–	STB 205–3	STB 205–3
Dusting brush		–	•	•	•	•	•
Upholstery nozzle		•	•	•	•	•	•
Crevice nozzle / crevice nozzle extension		•/–	•/–	•	•	•	•
Parquet floor brush		–	SBB Parquet–3	–	–	–	SBB 300–3
Mattress nozzle		–	–	–	–	–	–
Electrical connection							
Max. rated load	W	2000	2000	2200	2200	2200	2200

• = yes, existing
[1]) a = two-piece
b = telescopic
c = triscopic

Miele Ireland Limited
Broomhill Business Complex
Broomhill Road
Tallaght
Dublin 24
Tel.: +353 (0)1 461 0710
Fax: +353 (0)1 461 0797
www.miele.ie
info@miele.ie